

# LED EMERGENCY BUG EYE LIGHT

SPECIFICATION SHEET

STNE403



### Applications:

*Exhibit & Display, Commercial, or Residential Lighting Control*

### Features:

- Compact housing with (2) adjustable LEDs
- Light weight snap together design
- Plastic enclosure with 5VA flame retardant
- 3.6V maintenance-free, rechargeable Ni-Cad battery
- Self-diagnostic and self-testing option available
- High output option available (4W / 250lm)
- White or black finish
- Ceiling or wall mounted
- Universal 120-277V input
- Remote capable, must specify

### Description:

The 4 Watt Self Diagnostic / Self Testing LED Emergency Bug Eye Light provides 90 minutes of light from two adjustable heads for illuminating paths of egress upon failure of normal power. The emergency unit is available in higher lumen output and remote capability. Injection-molded thermoplastic ABS housing. Plastic enclosure with 5VA flame retardant. Quick connector design for easy installation. Two fully adjustable glare-free round heads for emergency lighting.

Upon power failure, additional battery requires an additional 24 hours to recharge. The plastic enclosure includes a top and side knockout for conduit application. Suitable for wall mounting or ceiling mounting. Available in White or Black Finish. 2w remote battery included.

### Specification:

<b>Voltage:</b>	120-277V AC
<b>Wattage:</b>	4w
<b>Color Temp.:</b>	6000k
<b>Brightness:</b>	250 Lumen
<b>Operating Temp.:</b>	10°C to 40°C ambient temperature
<b>Battery:</b>	NiCad 3.6V 3W maintenance-free
<b>Dimension:</b>	7-5/16" L x 2-3/16" x 4-1/4" H
<b>Environment:</b>	Damp Location
<b>Labels and Listings:</b>	cULus Listed for damp locations. cULus Listed and meets or exceeds all requirements in NFPA 70, NFPA 101 life safety code.
<b>Warranty</b>	3-Year Limited Warranty

